

Thermoflex RT

Thermoplastic counter material - non woven based - coated on one or both sides- with excellent shape reproduction and retention

Types available	Advice of application	Thickness
Coated on both sides		
Thermoflex RT C 26	medium hard counter	1.10 – 1.30 mm
Thermoflex RT C 36	medium hard counter	1.20 – 1.40 mm
Thermoflex RT C 46	medium hard counter	1.30 – 1.50 mm
One-piece counter -coated on one side		
Thermoflex RT C 35	medium hard counter	1.15 – 1.35 mm
Thermoflex RT C 45	medium hard counter	1.25 – 1.45 mm

Method for use: Use a Hot / Cold machine to get the best result:
Required interface temperature for bonding: 90 -100°C
Temperature at the hot mould: 130-160°C
Dwell time: 12 - 18 sec.

All data may vary according to substance of material and type of upper.

Delivery: In sheets, 10 sheets stapled together and edge trimmed on pallets or as counters – already cut and skived.

Cutting: In length direction as indicated on the sheets.

Skiving: Steel bottom roller and i.e. Fortuna skiving foot 361 HP

Premoulding: Can be fingermoulded for easy insertion

Sheet size: approx. 1.52 x 1.00m

Manufacturers warranty: Due to the great number of materials being used for shoe manufacturing the possibilities of chemical reactions and incompatibilities between components should be always tested beforehand. We are not liable for damages arising by non observance of our instructions for applications or from reactions beyond our influence and control.

Storing: Under normal conditions the storage is unlimited. Avoid direct storing in the sun. We guarantee for the goods 6 month after delivery date.