

Ultraline 1800

Counter lining material, used for heel base, reinforcements, decorative elements and insocks.

Ultraline is similar to natural leather and in certain aspects even superior to it. Among its distinguishing features are: high abrasion-resistance, slipping-resistance, high tear strength of stitched parts, good air- and water vapour-permeability, it gives comfort, thermal stability, easy working and can be used in all footwear manufacturing technologies.

<i>Types</i>	<i>Thickness</i>	
Ultraline 1807	0,7mm	plain
Ultraline 1807 P	0,7mm	one side coated with a special thermoplastic adhesive, ideal for greasy leathers.
Ultraline 1810	1,0mm	plain
Ultraline 1810 Z	1,0mm	one side coated with EVA-adhesive

Method for use: UL 1800 coated with thermoplastic adhesives requires an interface temperature of 100°C for bonding. The temperature can be reached with toe puff fusing presses at 130-150°C, 5 sec. at approx. 5 bar pressure.

Cutting: multiple-layer cuttings possible, clean-cut edges

Delivery: 10 sheets stapled together and edge trimmed on pallets or in rolls of 50m length

Sheet size: approx. 1,50 x 1,00m

Manufacturers warranty: Due to the great number of materials being used for shoe manufacturing the possibilities of chemical reactions and incompatibilities between components should be always tested beforehand. We are not liable for damages arising by non observance of our instructions for applications or from reactions beyond our influence and control.

Storing: Under normal conditions the storage is unlimited. Avoid direct storing in the sun. We guarantee for the goods 6 month after delivery date.